

Product Information

FLOOR & WALL ADHESIVE 101

AREA OF USAGE

Homogenous vinyl carpets and vinyl carpets with a back of glass or mineral fibre cork with PVC foil or foam on absorbing surfaces, linoleum, synthetic textile carpets with or without foam backs. *Beddings*; chip or wood fibre boards and dry concrete. Concrete with risk for moisture must be insulated against this, see HUS-AMA 83 (Swedish standard).

PROPERTIES

Open time up to 30 min. depending on temperature and humidity.

JOB SPECIFICATION

HUS-AMA 83 (Swedish standard) the temperature must be at least +18°C, the relative humidity maximum 60%. The bedding shall be dry, even and free from loose particles.

FLOOR, ABSORBING BEDDING

The adhesive should be spread on the surface with toothed spatulas. Carpets may immediately be laid out on the adhesive. Press the carpet with a roller to remove all air. *Tiles*; Wait for the adhesive to be so dry that there is no risk for the tiles to slip.

FLOOR, DENS BEDDING

The adhesive should be spread on the surface with toothed spatulas. Each carpet gore is laid out and the immediately lifted up to be exposed to air for 10-20 minutes. The gore is then put in place and fixed with a roller. If airing is not possible the adhesive must dry for 20-30 minutes before the gore is laid out. Check that the adhesive is active before the application.

WALLS

Apply the adhesive with a lamb wool rollers. The spreading or wallpaper hanging methods should be in accordance with the instructions for wall material. Use the spreading method for PVC foam mats.

TECHNICAL DATA

TYPE	Acrylic
COLOUR	Light yellow white
CONSISTENCY	Smooth and thixotropic
SPECIFIC GRAVITY	1,25
SOLVENT	Water
FIRE RATING	Non-flammable
DRY CONTENT	Ca 67%
MARKING	Handling and cleaning; When working with adhesives and glues you must always keep a good hygienic standard. When exposed to the skin then clean off with soap and water. Tools are cleaned in water before the adhesive tries. Dried adhesive is removed with a solvent.
	NOT THAT THE SOLVENTS ARE FLAMMABLE !
PERMANENCE	Good against water and alkali.
COLD RESISTANCE	Does not stand cooling below 0°C
JOB TEMPERATURE	Not below +18°C
TOOLS	Toothed spatula on floors and lamb wool roller on walls.

FLOOR&WALL ADHESIVE page 2

CONSUMPTION	4-6 sqm per litre
OPEN TIME	Wet gluing, ca 0-30 min., semi-dry gluing, 30-90 min. Dependent on temperature and relative humidity
STORAGE	At least 1 year in well sealed container in a frost free place
PACKAGING	1,0 litres bucket 5,0 litres bucket 15 litres bucket
ESTIMATED LIFETIME	At least 10 years providing that the joint has the correct measurements.
PROTECTION	The product is not classified as flammable or dangerous.

MAY NOT BE EXPOSED TO FROST !

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.