

# Product Information

## ***FLOOR VARNISH / FLOOR PAINT***

### **TYPE OF PRODUCT**

FLOOR VARNISH / FLOOR PAINT is a single component glossy air drying urethane-alkyd paint intended for wooden, linoleum and concrete floors indoors.

### **AREA OF USAGE**

FLOOR VARNISH / FLOOR PAINT is intended for floors with normal wear and tear.

### **PROPERTIES**

FLOOR VARNISH / FLOOR PAINT gives a glossy surface which is easy to take care of and resistant to wear and tear. The paint is easy to apply and evens out well.

### **TECHNICAL DATA**

<b>DENSITY</b>	Approx. 1,13 kg/litre
<b>GLOSS VALUE</b>	90
<b>DRYING TIME</b>	Dust dry after 1½ h, fully dry after 24hrs at +23°C and 55% air humidity
<b>DRY CONTENT</b>	Approx. 50%
<b>APPLICATION</b>	Brush or roller
<b>THINNING &amp; CLEANING OF TOOLS</b>	White spirit
<b>STORAGE</b>	At least 12 months in the unopened package
<b>PACKAGING</b>	2,5 litres
<b>OPACITY</b>	7 m <sup>2</sup> / litre
<b>MISCELLANEOUS</b>	The surfaces must be clean and dry. New concrete floors should have dried for at least 3 months, (cementhud) is machine-ground or washed with acid. The first cover should be thinned with 30% ligroin.
<b>ESTIMATED LIFETIME</b>	10 years, providing that the work is done correctly
<b>PROTECTION</b>	The product is flammable and hazardous. Use requires effective ventilation or breathing mask type A2

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.