

Product Information

MOUNTING ADHESIVE 4000

AREA OF USAGE

Multipurpose adhesive for all kinds of house- and building elements and details, e.g. floors, walls, ceilings and roofs, panels, windowsills, stairs, roof gutters, signs etc. The adhesive reduces the need for nails and screws and the finishing work with putty. Not cell plastic.

EXAMPLES

- * Gluing of parquet floors, panels, stairs etc
- * Mounting of fillet, windowsills etc.
- * Reduces use of nails

PROPERTIES

Gap filling elastic adhesive with excellent attaching properties against wood, plywood, fibreboard, laminate, cork, concrete, tile, iron, aluminium, sheet steel, PVC etc., resistant to moisture and changes in heat and withstands temperatures from -40°C to +100°C. Mounts to cold, wet and oily surfaces.

JOB SPECIFICATION

The adhesive is applied to one of the surfaces.

ADVANTAGES

- * Withstands moisture and heat (-40 to 0+100°C)
- * Attaches to cold, wet and oily surfaces
- * Forms an elastic bond with high strength
- * Reduces the need for putty fillings
- * Reduces the number of glues needed due to its versatility

TECHNICAL DATA

TYPE OF MATERIAL:	Synthetic rubber / resinoid
CONSISTENCY:	Smooth paste
STORAGE:	At least 1 year when the cartridge has not been opened. Do not allow it to freeze!
DRY CONTENT:	Approx. 60%
PACKAGING:	0,3 litre cartridge

SOLVENT:	Toluene and naphta
COLOURS:	Beige yellow
CONSUMPTION:	0,3 litre for approx. 20 meter
RESISTANCE TO COLD:	Cold resistant
FLAMMABILITY:	Flammable
DENSITY:	1,07 kg/l
WORKING TEMPERATURE:	-20 – +40°C
ESTIMATED LIFETIME:	At least 10 years providing that the work has been done correctly
PROTECTION:	The product is flammable and hazardous. When used, effective ventilation must be provided and/or breathing masks of type A2 must be worn.

The technical data we present as well as our directions and recommendations are all based on a number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we cannot accept responsibility of any kind for the results obtained when the product is used only for the product as such.