

# Product Information

## *Board Adhesive H<sub>2</sub>O*

### QUALITIES

Good adhesiveness against all building materials, wood, concrete, brick, plaster board, fibre board, plastered surfaces, metal etc., also on uneven surfaces.

### JOB SPECIFICATION

The surfaces must be clean and free from loose particles. Apply the glue strings approx. 55 mm in diameter with a space of 30 cm in between and approx. 2 cm from the outer edges, if possible in a zig-zag pattern. Adjust the detail and press strongly. Heavier boards should be fixated at the lower edge to avoid gliding during the hardening process. After 20-30 minutes make a final pressure with a hammer and wooden block.

## BOARD ADHESIVE H<sub>2</sub>O

### AREA OF USAGE

Installation of wall panels, matched boards, plastic laminates, plaster boards and fibre boards.

### TECHNICAL DATA

<b>TYPE OF MATERIAL</b>	Acrylic-Dispersion
<b>CONSISTENCY</b>	Soft paste
<b>STORAGE</b>	1 year in sealed container
<b>DRY MATTER</b>	Approx. 58%
<b>PACKAGING</b>	0,3 lit. cartridge
<b>SOLVENT</b>	Water
<b>CLEANING</b>	Water
<b>COLOUR</b>	Greywhite
<b>PROTECTION</b>	None
<b>CONSUMPTION</b>	0,3 lit. cartridge is sufficient to a string of glue of approx. 20 m
<b>SPEC.WEIGHT</b>	1,15 kg/liter
<b>RESISTANCE TO COLD</b>	<b>NOT</b> cold resistant
<b>ESTIMATED LIFETIME</b>	At least 10 years providing that the work has been done correctly.
<b>PROTECTION</b>	<b>The product is not classified as flammable or hazardous</b>

The technical data we present as well as our directions and recommendations are all based on a large number of test and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we cannot accept responsibility of any kind for the results obtained when the product is used.