

Product Information

CARPENTRY PUTTY

TYPE OF PRODUCT

CARPENTRY PUTTY is a water and latex based putty.

AREA OF USAGE

CARPENTRY PUTTY is intended for all kinds of puttying. The main use is carpentry and steel doors, but also for walls and ceilings where a surface with high finish is required.

PROPERTIES

A perfect foundation for varnish and carpentry colours. Excellent filling and adhesive properties. CARPENTRY PUTTY has insignificance smell and carries primers and finishing paints well.

JOB SPECIFICATION

All surfaces should be primed before puttying. Do not putty when the temperature is below +5°C. CARPENTRY PUTTY can be painted in a normal way (grinding and top coating).

TECHNICAL DATA

FILLING	Dolomite
SOLVENT	Water
CLEANING OF TOOLS	Water
DRY CONTENT	59 %
DENSITY	1,8
DRYING TIME	Approx. 1-2 hours, depending on thickness
STORAGE	Approx. 1 year, kept in a frost free place
FLAMMABILITY	Not flammable
PACKAGE	0,19 and 0,75 litre.
COLOUR	White
ESTIMATED LIFETIME	At least 10 years providing the work is done correctly
PROTECTION	The product is not classified as flammable or dangerous.

The technical data we present as well as our directions and recommendations are all based on a large number of tests as well as our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since we do not know the job conditions for the user and out of our control we cannot accept responsibility of any kind for the results obtained when the product is used.