

Product Information

FINISHING GLAZE

TYPE OF PRODUCT

FINISHING GLAZE is a thixotrop (nondrop) covering paint based on alkyd and oil, intended for outdoors painting on wood, un-treated or previous treated with oil- or alkyd paint. Not suited for surfaces previous treated with waterbased (acrylic) paints. FINISHING GLAZE gives a surface stable to weather and light and which is water-repellent. The paint attaches to galvanised or anti-corrosivetreated steel and iron details, which makes it possible to paint these at the same time as the woodsurface.

JOB SPECIFICATION

The foundation should be dry and clean. Scrap free from loose paint. Wash previous painted surfaces with paintsoda or ammoniac and rinse with water. Pre-treat chalked wood or wood with high absorption with OUTDOOR GLAZE (stir wall before use), apply with brush. For the first application dilute with white spirit, approx. 10%. Finish with undiluted paint.

TECHNICAL DATA

TYPE	Alkyd / oil
DRYING CONTENT	67 %
SOLVENT	White spirit
DENSITY	1,20
CONSISTENCY	Thixotrop
DRYING TIME	8 hours, coatable after 24 hours
FLAMMABILITY	approx. 40°C
HANDLING AND CLEANING	Avoid direct skincontact with the product due to the solvent. By skincontact wash with fatdissolving cleaners and water. Clean tools with white spirit.
WORKING TEMPERATURE	Down to +5°C
CONSUMPTION	Planned wood; 8-10m ² / litre and coating Unplanned wood; 4-6 m ² / litre and coating
STORAGE	2 years in well- sealed package
PACKAGING	1,0, 4,0 and 12,0L
ESTIMATED LIFETIME	At least 10 years, providing that the work is done correctly
PROTECTION	The product is flammable and hazardous. Painting presumes effective ventilation or use of mouth protection.

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.