

Product Information

WOOD ADHESIVE INDOORS

AREA OF USAGE

Gluing of all kinds of wood indoors – blocks, joints, pegs, mounting, edges etc.

PROPERTIES

WOOD ADHESIVE INDOORS is a thermoplastic, white, resinoid adhesive on PVAc base with a short open time and very high tensile strength. Non flammable and non toxic.

JOB SPECIFICATION

WOOD ADHESIVE INDOORS should be applied on both surfaces with a brush, spatula, roller or spray-gun. Immediately after the application the surfaces must be pressed together with clamps or a press.

Thinner; Water
Cleaning; Wet adhesive is removed with a wet cloth

TECHNICAL DATA

BASE	PVAc-dispersion
COLOUR	White
SPECIFIC GRAVITY	Approx 1,1 kg/litre
DRY CONTENT	Approx 43%
VISCOSITY	Approx 14.000-18.000 cp
OPEN TIME	15 minutes at +20 ² C
PRESSURE	1-5 kg/cm ²
PRESS-TIME	5-10 minutes for evenly planed wood. Hard and oily woods Or materials with strains require at least double time
HANDLING TIME	5 min. to approx 1 hr depending on amount of adhesive, type Of wood, temperature and hmidity
JOB TEMPERATURE	Minimum + 10 ⁰ C
TEMPERATURE PERMANENCE	-30 ⁰ C - +80 ⁰ C
STORAGE	2 year in well sealed container in a frost free place
PACKAGING	100ml., 250ml., 750ml., 5,0L. och 25L
CONSUMPTION	Approx 0,2 litre per m ²
TRANSPORTATION	Min. temperature -25 ⁰ C
ESTIMATED LIFETIME	At least 10 years providing that the joint has the correct measurements
PROTECTION	The product is not classified as flammable or dangerous.

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.