

# Product Information

## ***WALL PAINT 2 classic***

### **TYPE OF PRODUCT**

*Wall Paint 2 classic* is a dull water based and solvent free latex paint intended for painting and re-painting of walls and ceilings indoors.

### **AREA OF USAGE**

*Wall Paint 2 classic* is mostly used in bedrooms, living rooms, lounges etc. It is suitable for e.g. plaster, concrete, sand glazed surfaces, wood fibre, chip, particle and gypsum boards, fabric, wallpapers and previously painted surfaces.

### **PROPERTIES**

*Wall Paint 2 classic* has a slight and fully harmless smell during application and when drying. It is drying fast and does not yellow with age.

### **PAINTING THE FIRST TIME**

*Pre-treatment*; Sand glazed surfaces, plaster, concrete, wood fibre, chip, particle and gypsum boards and fabrics must be rid of all dirt, dust and loose particles before painting.

*Priming*; Prime when needed and make sure that the surface is saturated, i.e. highly absorbing surfaces will need more primer than low absorbing. Hard wood, e.g. oak, beech and red wood, might not need priming. The *Wall Paint 2 classic* diluted with 10% water may with advantage be used for priming. When the surface is sufficiently primed then it should be sanded to eliminate risen fibres.

*Finishing*; Apply 1 or 2 coats of *Wall Paint 2 classic*.

### **RE-PAINTING**

*Pre-treatment of pre-painted surfaces*; Wash if needed. Glossy surfaces should be dulled with medium fine grinding paper to obtain optimal adhesion between the layers.

*Whitewashed surfaces*; Scrape and brush the surface down to a firm bedding then dust the surface or wash it with water.

*Limed Surfaces*; Wash clean with water.

*Finishing*; Apply 1 or 2 coats of *Wall Paint 2 classic*.

*Thinning*; Should normally not be thinned but can be diluted with water.

*Cleaning*; The tools should be cleaned with water immediately after use.

*Tools*; Is best applied with roller or brush.

## WALL PAINT 2 classic, Page 2

**NOTE! Do not paint on surfaces with a temperature lower than +5°C.**

### TECHNICAL DATA

<b>COLOURS</b>	View colour chart
<b>PACKAGING</b>	2,5 Litre
<b>CONSUMPTION</b>	5-8 m <sup>2</sup> /litre and coating
<b>BINDING AGENT</b>	Acrylic latex
<b>DENSITY</b>	1,54
<b>VISCOSITY</b>	Approx. 20.000 cp.
<b>DRY CONTENT</b>	Approx. 59 %
<b>DRYING TIME</b>	Sticky free after approx. 30 min. Coatable after 3 hours
<b>GLOSS</b>	2 units
<b>STORAGE</b>	To be stored frost-free
<b>FLAMMABILITY</b>	Not flammable
<b>ESTIMATED LIFETIME</b>	At least 10 years, providing that the work is done correctly
<b>PROTECTION</b>	The product is not flammable or hazardous

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.