

Product Information

WALL PAINT 20

TYPE OF PRODUCT

Wall Paint 20 is a water based acrylic latex paint intended for painting and re-painting of walls and ceilings indoors when a semi dull washable finish is required.

AREA OF USAGE

Wall Paint 20 is mostly used in kitchens, entrance halls and staircases. It is suitable for e.g. plaster concrete, sand glazed surfaces, wood fibre, chip, particle and gypsumboards, fabric, wall papers and previously painted surfaces.

PROPERTIES

Wall Paint 20 has excellent adhesion to e.g. surfaces painted with latex, alkyd and oil paints which makes it highly suitable for repair painting. It has a slight smell during painting and when drying. It gives a round and soft edge. It is drying fast and does not yellow when ageing. The opacity is excellent.

PAINTING THE FIRST TIME

Pre-treatment; Sand glazed surfaces, plaster, concrete, wood fibre, chip, particle and gypsum boards and fabrics must be rid of all dirt, dust and loose particles.

Finishing; Apply 1 or 2 coats of *Wall Paint 20*.

RE-PAINTING

Pre-treatment of pre-painted surfaces; Wash with Paint Soda or Paint Wash. Rinse carefully with water. Glossy surfaces should be dulled with medium fine grinding paper to obtain optimal adhesion between the layers.

Paper&Fabric wallpapers, wall plastics; Make sure the wallpaper is firm to the wall. It must be re-glued where lose. Wash with paint wash. Rinse carefully with water.

Finishing; Apply 1 or 2 coats of *Wall Paint 20*.

Thinning; Should normally not be thinned but can be diluted with water.

Cleaning; The tools should be cleaned with water immediately after use.

Application; Normally applied with roller or sprayer and is filtered to allow high pressure spraying.

NOTE ! Do not paint surfaces with a temperature lower than +5°C.

Certain wall plastic qualities may be difficult to paint. Make a test when in doubt and check the adhesion. Do not expose the paint to a lot of water until after some time. The surface is fully washable after approx. 1 month.

WALL PAINT 20, Page 2

TECHNICAL DATA

COLOUR	White
PACKAGING	1,0, 4,0, 9,0 and 12 litres
CONSUMPTION	6-8 m ² / litre and coating
BINDING AGENT	Acrylic latex
SOLVENT	Water
DENSITY	Approx 1.25 kg/litre
VISCOSITY	Approx. 33.000 cp.
DRY CONTENT	Approx. 49%
DRYING TIME	Sticky free after approx. 30 min. Coatable after approx. 3 hours.
GLOSS VALUE(SS184184 Sweden)	20 units
WASHABLE(SS184164 SwedeN)	More than 2000 cycles
STORAGE	To be stored frost free
FLAMMABILITY	Not flammable
ESTIMAED LIFETIME	At least 10 years providing that the work is done correctly
PROTECTION	The product is not flammable or hazardous.

The technical data we present as well s ouor directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.