

# Product Information

## WALL PAINT 40

### TYPE OF PRODUCT

*Wall Paint 40* is a water based latex paint intended for painting and re-painting of walls and ceilings indoors when a semi glossy washable finish is required.

### AREA OF USAGE

*Wall Paint 40* has a well-balanced glossy finish for use in kitchens, entrance halls and bathrooms, schools, corridors etc.

It is highly suitable for plaster, concrete, sand glazed surfaces, wood fibre, chip, particle and gypsumboards, fabric, wall plastics and previously painted surfaces.

### PROPERTIES

*Wall Paint 40* has excellent adhesion to e.g. surfaces painted with latex, alkyd and oil paints which makes it highly suitable for repair painting. It has a slight smell during painting and when drying. It gives a rounder and softer edge compared to PVA-latex paints. It is drying fast and does not yellow when ageing. The opacity is excellent.

### PAINTING THE FIRST TIME

*Pre-treatment;* The surfaces must be rid of all dirt, dust and loose particles. Prime with *Wall Paint 40*.

*Filling;* Fill joints, seams, nail holes and other irregularities with *Wall Putty*. Smooth with medium fine grinding paper.

*Finishing;* Apply 1 or 2 coats of *Wall Paint 40*

### RE-PAINTING

*Pre-treatment of pre-painted surfaces;* Wash with *Paint Soda*. Rinse carefully with water. Glossy surfaces should be dulled with medium fine grinding paper to obtain optimal adhesion between the layers.

*Whitewashed surfaces;* Wash clean with water.

*Limed surfaces;* Scrape and brush the surface down to a firm bedding then dust the surface or wash it with water.

*Paper & Fabric wallpapers, wall plastics;* Make sure the wallpaper is firm to the wall. It must be re-glued where loose. Wash with Liwell's *Paint Soda* to which is added approx. 5% ammoniac. Rinse carefully with water.

*Filling;* Use *Wall Putty*.

*Finishing;* Apply 1 or 2 coats of *Wall Paint 40*

*Thinning;* Should normally not be thinned but can be diluted with water.

*Cleaning;* The tools should be cleaned with water immediately after use.

*Application;* Normally applied with roller or sprayer and is filtered to allow high pressure spraying.

## WALL PAINT 40, Page 2

### NOTE!

Do not paint on surfaces with a temperature lower than +5°C.

Certain wall plastic qualities may be difficult to paint. Make a test when in doubt and check the adhesion. Do not expose the paint to a lot of water until after some time. The surface is fully washable after approx. 1 month.

### TECHNICAL DATA;

<b>COLOUR</b>	White
<b>PACKAGING</b>	2,5 litres
<b>CONSUMPTION</b>	6-8 m <sup>2</sup> / litre and coating
<b>BINDING AGENT</b>	Acrylic latex
<b>SOLVENT</b>	Water
<b>DENSITY</b>	Approx. 1,26 kg/litre
<b>VISCOSITY</b>	Approx. 34.000 cp.
<b>DRY CONTENT</b>	Approx. 49 %
<b>DRYING TIME</b>	Sticky free after approx. 30 min. Coatable after approx. 3 hours.
<b>GLOSS VALUE (SS184184 Sweden)</b>	40 units
<b>WASHABLE(SS184164 Sweden)</b>	More than 2000 cycles
<b>STORAGE</b>	To be stored frost-free
<b>FLAMMABILITY</b>	Not flammable
<b>ESTIMATED LIFETIME</b>	At least 10 years, providing that the work is done correctly
<b>PROTECTION</b>	The product is not flammable or hazardous.

The technical data we present as well as our directions and recommendations are all based on a large number of tests and our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since the job conditions for the user are out of our control we can not accept responsibility of any kind for the results obtained when the product is used.