

Product Information

WALL PUTTY light

TYPE OF PRODUCT

WALL PUTTY is water and latex based fine graded traditional putty for use indoors. Where a very smooth surface is required.

AREA OF USAGE

WALL PUTTY is for application by hand for e.g. concrete, grout, bricks, fabric (even painted) and for putting gypsum boards and wallpaper. When putting joints on boards a strip of paper can be placed directly in the putty.

PROPERTIES

WALL PUTTY gives a tight, smooth surface and is very easy to grind. WALL PUTTY has excellent filling properties. WALL PUTTY is not suitable for carpentry, where CARPENTRY PUTTY is recommended.

TREATMENT

The surface should be dry. Cover big holes first. Spread WALL PUTTY with a steel putty knife. The number of treatments depends on how thick layer is needed.

WORKING ADVISE

- * When grinding use mouth protection.
- * Do not putty on surface with a temperature lower than +5°C.
- * Clean tools with water immediately after use.

TECHNICAL DATA

COLOUR	White
PACKAGE	0,5 , 4,0 and 10,0 litres
CONSUMPTION	0,3-0,6 per litre and m ² , depending on foundation
SOLVENT	Water
DENSITY	1,05
DRYING TIME	Approx. 2 hours. Dry right through after 24 hours.
STORAGE	In a cool but frost free place.
FLAMMABILITY	Not flammable
PROTECTION	The product is not classified as flammable or dangerous.

The technical data we present as well as our directions and recommendations are all based on a large number of tests as well as our experience. They are intended as guidance for the user to find the most suitable job method and to obtain an optimal result. Since we do not know the job conditions for the user and out of our control we cannot accept responsibility of any kind for the results obtained when the product is used.